

CMS120N080B

SiC N-Channel 1200-V (D-S) MOSFET

Features

- High speed switching
- High blocking voltage
- Fast reverse recovery


Benefits

- Low capacitance
- High system efficiency
- Easy to parallel Applications


Typical Applications

- Solar inverters
- Switch mode power supplies, UPS
- Induction heating and welding
- EV charging stations
- High voltage DC/DC converters
- Motor drive

Package type : TO-263-7




Package Dimension



Symbol	Dimensions		Symbol	Dimensions	
	Millimeters			Millimeters	
	Min	Max		Min	Max
A	4.40	4.64	D1	8.39	8.89
A1	1.22	1.32	D2	---	1.27
b	0.56	0.81	e	---	1.27
c	0.38	0.76	E	10.04	10.41
D	---	14.35	L	---	1.98

Marking



RoHS Compliant

CMS120N080B

SiC N-Channel 1200-V (D-S) MOSFET

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Absolute Maximum Ratings

Symbol	Parameter	Value	Units
V_{DS}	Drain-Source Voltage	1200	V
V_{GS}	Gate-Source Voltage	-5/20	V
I_D	Continuous Drain Current ($T_C=25^{\circ}C$)	35	A
	Continuous Drain Current($T_C=100^{\circ}C$)	25	A
$I_{D,pulse}$	Pulsed Drain Current	80	A
P_{tot}	Power Dissipation ($T_C=25^{\circ}C$)	188	W
E_{AS}	Single Pulse Avalanche Energy, $I_{AS}=20A$, $V=50V$, $L=1mH$	200	mJ
T_J/T_{STG}	Operating Junction and Storage Temperature	-55...175	$^{\circ}C$

Thermal Resistance Ratings

Symbol	Parameter	Maximum	Units
$R_{\theta JA}$	Maximum Junction-to-Ambient	40	$^{\circ}C/W$
$R_{\theta JC}$	Maximum Junction-to-Case	0.8	$^{\circ}C/W$

Static Electrical Characteristics, ($T_J=25^{\circ}C$ unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}$, $I_D=10mA$	2.0	2.8	4.0	V
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{GS}=0V$, $I_D=1mA$	1200	-	-	V
I_{GSS+}	Gate-Source Leakage Current	$V_{DS}=0V$, $V_{GS}=20V$	-	0.1	100	nA
I_{GSS-}		$V_{DS}=0V$, $V_{GS}=-5V$	-	-	-100	
I_{DSS}	Drain-Source Leakage Current	$V_{DS}=1200V$, $V_{GS}=0V$	-	-	1.0	μA
		$V_{DS}=1200V$, $V_{GS}=0V$, $T_J=175^{\circ}C$	-	1.0	-	
$R_{DS(on)}$	Static Drain-Source On-Resistance	$V_{GS}=20V$, $I_D=20A$	-	77	100	m Ω
		$V_{GS}=20V$, $I_D=10A$	-	71	90	
		$V_{GS}=20V$, $I_D=20A$, $T_J=125^{\circ}C$	-	106	-	
		$V_{GS}=20V$, $I_D=20A$, $T_J=175^{\circ}C$	-	134	-	
R_g	Gate Input Resistance	$f=1MHz$, $V_{AC}=25mV$, D-S short	-	3.0	-	Ω

CMS120N080B

SiC N-Channel 1200-V (D-S) MOSFET

AC Electrical Characteristics, ($T_J=25^{\circ}\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
Q_g	Total Gate Charge	$V_{DD}=800\text{ V}$, $I_{DS}=20\text{ A}$, $V_{GS}=-5/20\text{ V}$	-	61	-	nC
Q_{gs}	Gate-Source Charge		-	24	-	
Q_{gd}	Gate-Drain Charge		-	14	-	
$t_{d(on)}$	Turn-On Delay Time	$V_{DD}=800\text{ V}$, $I_{DS}=20\text{ A}$, $R_{G(ext)}=2.5\ \Omega$, $V_{GS}=-5/+20\text{ V}$, $L=975\ \mu\text{H}$	-	9	-	ns
t_r	Rise Time		-	4	-	
$t_{d(off)}$	Turn-Off Delay Time		-	15	-	
t_f	Fall Time		-	10	-	
C_{ISS}	Input Capacitance	$V_{GS}=0\text{ V}$, $V_{DS}=1000\text{ V}$, $f=200\text{ kHz}$, $V_{AC}=25\text{ mV}$	-	1377	-	pF
C_{OSS}	Output Capacitance		-	62	-	
C_{RSS}	Reverse Transfer Capacitance		-	4	-	
E_{OSS}	Coss Stored Energy		-	38	-	μJ
E_{on}	Turn-On Switching Energy	$V_{DD}=800\text{ V}$, $I_{DS}=20\text{ A}$, $R_{G(ext)}=2.5\ \Omega$, $V_{GS}=-5/+20\text{ V}$, $L=975\ \mu\text{H}$	-	208	-	
E_{off}	Turn-Off Switching Energy		-	25	-	
E_{tot}	Total Switching Energy		-	233	-	

Body Diode Characteristics, ($T_J=25^{\circ}\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
I_S	Max Continuous Diode Forward Current	$V_{GS}=-5\text{ V}$, $T_C=25^{\circ}\text{C}$	-	-	43	A
V_{SD}	Diode Forward Voltage	$V_{GS}=-5\text{ V}$, $I_S=10\text{ A}$	-	3.8	-	V
t_{rr}	Reverse Recovery Time	$I_S=20\text{ A}$, $V_R=800\text{ V}$, $V_{GS}=-5\text{ V}$, $di/dt=8\text{ A}/\mu\text{s}$	-	8	-	ns
Q_{rr}	Reverse Recovery Charge		-	130	-	nC
I_{rrm}	Peak Reverse Recovery Current		-	29	-	A

- Typical Electrical Characteristics




FIG.1-Output Characteristics $T_j = -55^\circ\text{C}$




FIG.2- Output Characteristics $T_j = 25^\circ\text{C}$




FIG.3- Output Characteristics $T_j = 125^\circ\text{C}$




FIG.4- Output Characteristics $T_j = 175^\circ\text{C}$




FIG.5-Normalized $R_{DS(on)}$ vs. Temperature T_j




FIG.6- On-Resistance vs. Drain Current For Various Temperature

Typical Electrical Characteristics




FIG.7- On-Resistance vs. Temperature For Various Gate Voltages




FIG.8- Transfer Characteristic for Various Junction Temperatures




FIG.9- Body Diode Characteristics at $T_J = -55^{\circ}C$




FIG.10- Body Diode Characteristics at $T_J = 25^{\circ}C$




FIG.11- Body Diode Characteristics at $T_J = 175^{\circ}C$




FIG.12- Continuous Drain Current Derating vs. T_C

- Typical Electrical Characteristics




FIG.13-Threshold Voltage vs. Temperature




FIG.12- Gate Charge Characteristics




FIG.15- Output Capacitor Stored Energy




FIG.16- Capacitance vs Drain-Source Voltage




FIG.17- Clamped Inductive Switching Energy vs. Drain Current Various










FIG.18- Clamped Inductive Switching Energy vs. $R_{G(ext)}$

CMS120N080B

SiC N-Channel 1200-V (D-S) MOSFET



• Typical Electrical Characteristics



CMS120N080B

SiC N-Channel 1200-V (D-S) MOSFET

- Typical Electrical Characteristics



CMS120N080B

SiC N-Channel 1200-V (D-S) MOSFET

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Bruckewell Technology Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Bruckewell"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. Bruckewell makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Bruckewell disclaims

- (i) Any and all liability arising out of the application or use of any product.
- (ii) Any and all liability, including without limitation special, consequential or incidental damages.
- (iii) Any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Bruckewell's knowledge of typical requirements that are often placed on Bruckewell products in generic applications.

Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time.

Product specifications do not expand or otherwise modify Bruckewell's terms and conditions of purchase, including but not limited to the warranty expressed therein.